

EPIGAP Optronics GmbH

Koepenicker Str. 325b
D-12555 Berlin
Fon: +49 (0)30 657637 60
Fax: +49 (0)30 657637 70
sales@epigap-optronic.de




Data Sheet

LED Chip red

EOLC-650-24

Rev. 02, 2017

Radiation	Type	Electrodes
red	AlGaAs / AlGaAs (DDH)	n (cathode) up



Optical and Electrical Characteristics

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Test cond.	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F = 20 \text{ mA}$	V_F		1.9	2.2	V
Reverse current	$V_R = 5 \text{ V}$	I_R			10	μA
Radiant power*	$I_F = 20 \text{ mA}$	Φ_e	0.8	1.2		mW
Peak wavelength	$I_F = 20 \text{ mA}$	λ_p	640	650	660	nm
FWHM	$I_F = 20 \text{ mA}$	$\Delta\lambda_{0.5}$		21		nm
Switching time	$I_F = 20 \text{ mA}$	t_r, t_f		100		ns

*Measured on bare chip on TO-18 header

Packing

Chips on adhesive film with wire-bond side top

Art. No. 112 113



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.