

EPIGAP Optronik GmbH

Koepenicker Str. 325
 D-12555 Berlin
 Fon: +49 (0)30 657637 60
 Fax: +49 (0)30 657637 70
 sales@epigap-optronic.de



Data sheet

page 1 of 2

Infrared LED

EOLD-1300-015

Rev. 02, 2017

Radiation	Type	Case
Infrared	InGaAs/InP, MQW	TO-46 with glass lens cap

	Description:
<p>① Cathode ② Anode</p> <p>Dimensions (Unit:mm)</p>	Application:
	<p>High-power, high speed, narrow beam angle, high reliability</p> <p>Optical switches, optical communication, safety equipment, automation</p>

Maximum Ratings

T_{amb} = 25°C, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current		I _F	100	mA
Peak forward current (pulse)	t ≤ 50 μs, T = 100 μs	I _{FM}	200	mA
Reverse voltage	I _R = 10 μA	V _R	5	V
Power dissipation		P _D	115	mW
Operating temperature range		T _{amb}	-20 to +85	°C
Storage temperature range		T _{stg}	-30 to +100	°C
Lead soldering temperature	t < 5 s, 3 mm from case	T _{slg}	260	°C
Junction temperature		T _J	100	°C



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

EPIGAP Optronic GmbH

Koepenicker Str. 325
D-12555 Berlin
Fon: +49 (0)30 657637 60
Fax: +49 (0)30 657637 70
sales@epigap-optronic.de



Data sheet

page 2 of 2

Infrared LED


EOLD-1300-015

Rev. 02, 2017

Optical and Electrical Characteristics

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F = 20\text{ mA}$		0.85	1.05	V
Forward voltage	V_F	$I_F = 100\text{ mA}$		0.95	1.15	V
Radiant power	Φ_e	$I_F = 20\text{ mA}$	1.2	1.6		mW
Radiant power	Φ_e	$I_F = 100\text{ mA}$		8		mW
Peak wavelength	λ_p	$I_F = 20\text{ mA}$	1270	1300	1330	nm
FWHM	$\Delta\lambda_{0,5}$	$I_F = 20\text{ mA}$		85		nm
Viewing angle	φ	$I_F = 20\text{ mA}$		6		deg.
Switching times	t_r, t_f	$I_F = 20\text{ mA}$		25; 40		ns



Typical radiation pattern

Art. No. 430 053



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.