

EPIGAP Optronik GmbH

Koepenicker Str. 325
 D-12555 Berlin
 Fon: +49 (0)30 657637 60
 Fax: +49 (0)30 657637 70
 sales@epigap-optronic.de



Data sheet

page 1 of 2

Infrared LED

EOLD-1720-095

Rev. 02, 2017

Radiation	Type	Case
Infrared	InGaAs/InP, MQW	TO-46 package with flat window

Description:
High-power, high speed, wide beam angle, high reliability
Applications:
Optical switches, optical communication, safety equipment, automation, applications requiring high output and precise optical / mechanical axis alignment.

1- cathode, 2 -anode, all dimensions in mm,
 tolerance: ±0.2

Description:

High-power, high speed, wide beam angle, high reliability

Applications:

Optical switches, optical communication, safety equipment, automation, applications requiring high output and precise optical / mechanical axis alignment.

Maximum Ratings

T_{amb} = 25°C, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current		I _F	100	mA
Peak forward current (pulse)	t ≤ 10 μs, T = 10 ms	I _{FM}	200	mA
Reverse voltage	I _R = 100 μA	V _R	5	V
Power dissipation		P _D	100	mW
Operating temperature range		T _{amb}	-25 to +85	°C
Storage temperature range		T _{stg}	-30 to +100	°C
Lead soldering temperature	t < 5 s, 3 mm from case	T _{slg}	260	°C
Junction temperature		T _J	100	°C



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

EPIGAP Optronik GmbH

Koepenicker Str. 325
D-12555 Berlin
Fon: +49 (0)30 657637 60
Fax: +49 (0)30 657637 70
sales@epigap-optronic.de



Data sheet

page 2 of 2

Infrared LED


EOLD-1720-095

Rev. 02, 2017

Optical and Electrical Characteristics

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F = 20 \text{ mA}$		0.7		V
Reverse current	I_R	$V_R = 5 \text{ V}$		100		μA
Radiant power	Φ_e	$I_F = 20 \text{ mA}$		1		mW
Peak wavelength	λ_p	$I_F = 20 \text{ mA}$		1720		nm
FWHM	$\Delta\lambda_{0.5}$	$I_F = 20 \text{ mA}$		130		nm
Viewing angle	φ	$I_F = 20 \text{ mA}$		50		deg.
Switching time	t_r, t_f	$I_F = 20 \text{ mA}$		15		ns



Radiation pattern

Art. No. 134 098



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.