

# EPIGAP Optronik GmbH

Koepenicker Str. 325  
 D-12555 Berlin  
 Fon: +49 (0)30 657637 60  
 Fax: +49 (0)30 657637 70  
 sales@epigap-optronic.de



## Data Sheet

page 1 of 4

### High Power SMD LED

### EOLS-855-227

Rev. 01, 2020

Radiation	Type	Case
Infrared	AlGaAs	SMD 6046 (2418), ceramics

All dimensions in mm

**Description:**

- size: 6.0(L) x 4.6(W) x 4.3(H) mm
- circuit substrate: AlN ceramics
- with glass lens, view angle 20°
- soldering pads: gold plated; only for reflow soldering
- marking at anode, ROHS and REACH conform

### Maximum Ratings

T<sub>amb</sub> = 25°C, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current		I <sub>F</sub>	1000	mA
Peak forward current	t <sub>p</sub> ≤ 100 μs, τ = 1:10	I <sub>FM</sub>	1000	mA
Reverse voltage		V <sub>R</sub>	5	V
Thermal resistance		R <sub>th_JA</sub>	5	K/W
Operating temperature range		T <sub>amb</sub>	-40 to +85	°C
Storage temperature range		T <sub>stg</sub>	-40 to +85	°C

Electrostatic discharge classification (MIL-STD-883) - class 1

### Optical and Electrical Characteristics

T<sub>amb</sub> = 25°C, unless otherwise specified

Parameter	Symbol	Conditions	Min	typ	max	Unit
Forward voltage	V <sub>F</sub>	I <sub>F</sub> = 350 mA		1.6	1.9	V
Radiant power*	Φ <sub>e</sub>	I <sub>F</sub> = 350 mA				mW
Radiant intensity*	I <sub>e</sub>	I <sub>F</sub> = 350 mA		910		mW/sr
Peak wavelength	λ <sub>p</sub>	I <sub>F</sub> = 350 mA	840	855	870	nm
FWHM	Δλ <sub>0,5</sub>	I <sub>F</sub> = 350 mA		25		nm
Reverse current	I <sub>R</sub>	I <sub>R</sub> = 5 V			100	μA

\*measured on star board



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

# EPIGAP Optronik GmbH

Koepenicker Str. 325  
D-12555 Berlin  
Fon: +49 (0)30 657637 60  
Fax: +49 (0)30 657637 70  
sales@epigap-optronic.de




## Data Sheet


### High Power SMD LED

### EOLS-855-227

page 2 of 4  
Rev. 01, 2020



Forward current vs. forward voltage



Typical radiation spectrum at 350 mA




We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.


**Data Sheet**

**High Power SMD LED**


**EOLS-855-227**



**Radiant power vs. forward current**



**Peak wavelength vs. forward current**




**Radiation pattern**




**Data Sheet**

**High Power SMD LED**


**EOLS-855-227**



**Maximum allowable forward current vs. operating temperature**



**Recommended reflow soldering profile**



**Recommended soldering pattern**

Thermal pad needs to be connected to a heat sink with less than 10 K/W thermal resistance.

Art. No. 133 284

