


Data Sheet

Infrared photodiode

EOPD-1300-0-0.3-1

Rev. 04, 2016

| Spectral range | Type | Case |
|----------------|--------|-------------------------|
| Infrared | InGaAs | TO-46, glass window cap |



①Case ②Cathode ③Anode

Features:

- High speed response (max. 2 Gbps)
 - High reliability
 - High sensitivity

Applications:

- High speed optical communications
 - Optical LAN
 - Optical switches
 - Ethernet fiber channel

All dimensions in mm, tolerance: ± 0.2

Electro-optical characteristics:

T_{amb} ≡ 25°C, unless otherwise specified

| Parameters | Symbol | Min | Typ | Max | Unit | Test conditions |
|---------------------------|-----------|-----|-------------------|------|---------|--|
| Active area size | | | \varnothing 0.3 | | mm | |
| Sensitivity range | λ | 800 | | 1750 | nm | $V_R=0$ V |
| Dark current | I_D | | | 1 | μ A | $V_R=2$ V |
| Junction capacitance | C_j | | 15 | | pF | $V_R=0$ V |
| Photocurrent @ 1300 nm | I_{PH} | | 30 | | μ A | $V_R=5$ V, $E_e=1$ mW/cm ² |
| Breakdown voltage | V_{BR} | 5 | | | V | $I_R=10$ μ A |

Absolute maximum ratings

| Parameters | Min | Max | Unit |
|-----------------------|-----|------|------|
| Operating temperature | -40 | +85 | °C |
| Storage temperature | -40 | +125 | °C |

Art. No. 143 049

We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

